SECTION 1 - IDENTIFICATION

MANUF / DIST:

PREPARER / CONTACT: PREPARER PHONE: 24 HOUR EMERGENCY PHONE:


TRADE NAME / SYNONYMS:

CHEMICAL NAME / SYNONYMS: CHEMICAL FAMILY: FORMULA: PRODUCT CODE: MAJESTIC SOLUTIONS DISTRIBUTING CO 1001 CORPORATION PARKWAY SUITE 110 RALEIGH, N.C. 27610 PHIL TODD 919-212-1150 INFOTRAC 1-800-535-5053

PARTS WASH POWDER

NOT APPLICABLE NOT APPLICABLE PROPRIETARY NOT APPLICABLE

SECTION 2. HAZARDOUS IDENTIFICATION HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:







Signal Word: WARNING! - FOR HEALTH EFFECTS (Acute and Chronic): SEE SECTION 11

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29§1910.1200 (i)-(13) [exact % withheld as trade secret]							
CHEMICAL / COMMON NAME	CAS#	PERCENTAGE	PEL-OSHA	TLV-ACGIH			
Crystalline Silicate	6834-92-0	>1	N/A	N/A			
Surface Active Agents Non hazardous content	(PROPRIETARY)	>1	N/A	N/A			

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA):

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES:

- a) Skin Immediately flush skin with lots of running water for at least 30 minutes. Remove contaminated clothing and shoes, Wash before reuse.
- b) Eyes Flush immediately with large quantities of running water for at least 15 minutes. Consult physician.
- c) Inhalation If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
- d) Ingestion Do not induce vomiting. Call physician immediately. If conscious, give lots of water or milk. Do not give anything by mouth to an unconscious or convulsing person.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT (Method Used): None	FLAMMABLE LIMITS:	LEL = N/A	UEL= N/A
---------------------------------	-------------------	-----------	----------

EXTINGUISHING MEDIA: Not considered a fire hazard. HAZARDOUS DECOMPOSITION PRODUCTS: None

SPECIAL FIRE FIGHTING PROCEDURES: N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Absorb the large spill on suitable absorbent. Wash the residue down the drain or pit with plenty of water. Small spills can be flushed down the drain with plenty of water.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- a) Do not store under freezing conditions or above 120 degrees F.
- b) Protect from physical damage and keep tightly closed.
- c) Do not store near acids or acidic materials and oxidizers.

MAINTENANCE PRECAUTIONS:

N/A

OTHER PRECAUTIONS: Containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: LOCAL EXHAUST: Below TLV(s) MECHANICAL (GENERAL): NONE SPECIAL: N/A OTHER: N/A

RESPIRATORY PROTECTION:

An appropriate NIOSH approved hydrocarbon canister or respirator for organic DUST vapor should be worn if needed.

PROTECTIVE GLOVES:

Wear: Resistant gloves such as nitrile, rubber, PVC, etc.

DHL rev 1/28/2021

MAJESTIC SOLUTIONS DISTRIBUTING CO

OTHER PROTECTIVE EQUIPMENT:

Eye wash and quick drench facilities.

OTHER ENGINEERING CONTROLS: None Known

WORK PRACTICES:

Eye wash fountain and safety shower should be easily accessible. Discard properly such items as rags and trash soaked with the product. Provide adequate ventilation.

HYGIENIC PRACTICES:

Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F):	N/A	SPECIFIC GRAVITY (WATER=1):	1.04
VAPOR PRESSURE (mmHg):	N/D	PERCENT VOLATILE BY VOLUME (%):	> 90
VAPOR DENSITY (AIR=1):	N/D	EVAPORATION RATE (WATER=1):	1
pH	8-10	Melting pt-N/A /freezing pt 30+-°Relative density 1088° C	
SOLUBILITY IN WATER:	100%.	APPEARANCE, ODOR, VISCOSITY:: White P	owder

SECTION 10 - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION WILL NOT OCCUR THIS PRODUCT IS STABLE CONDITIONS TO AVOID FOR STABILITY: N/A INCOMPATIBILITY (Material To Avoid): Avoid contact with acids and strong oxidizers such as permanganate, chlorine, etc.

SECTION 11 - TOXICOLOGICAL INFORMATION

FOR NUMERICAL MEASURES OF TOXICITY SEE SECTION 3, COLUMNS (PEL-OSHA)AND(TLV-ACGIH)

HEALTH EFFECTS (Acute and Chronic):

Acute:

- a) Eyes -Can cause severe irritation, redness, tearing, blurred vision.
- b) Skin Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis
- c) Inhalation Breathing of dust can cause mild to severe irritation of nasal or respiratory passage.
- d) Ingestion Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic

PRIMARY ROUTES OF ENTRY:

a) Skin b) Inhalation

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product. THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA)

SECTION 12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: N/A

100% BIODEGRADABLE ECOTOXICOLOGICAL INFORMATION: N/A

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS:

Dispose of according to local, state and federal regulations for biodegradable detergents.

SECTION 14 - TRANSPORT INFORMATION CRYSATALLINE SILICATE, 8, UN-3262, PG III, MINOR DANGER

SECTION 15 - REGULATORY INFORMATION

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA):

SECTION 16 - OTHER INFORMATION

KEEP OUT OF THE REACH OF CHILDREN!

IN CLOSE COOPERATION OF THE US GOVERNMENT'S PAPER REDUCTION ACT, AND ALSO IN EFFORT TO PROVIDE FULL AND COMPLETE INFORMATION AS SUGGESTED BY THE OSHA GUIDELINES, AND KEEPING IN ALIGNMENT WITH THE SOCIETY for CHEMICAL HAZARD COMMUNICATION (SCHC) AND WE HAVE BEEN ABLE TO KEEP ALL IN 4 PAGES..

THESE SDS SHEETS ARE WRITTEN IN AN EFFORT TO PROVIDE INFORMATION TO THE WORKER IN THE WORKPLACE AND IN SUCH A WAY IT CAN BE UNDERSTOOD.

We have enjoyed many compliments as to the readability and understandable content, and take great pride in providing these Safety Data Sheets to the use of our customers.

The International Labour Organization has suggested 16 sections of the sheets, and we have re adjusted the 8 part, and rearranged the information, and renamed the sheets from MATERIAL Safety Data Sheets to SAFETY DATA SHEETS. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE. IT IS PROVIDED FOR A CONTINUING SAFETY PROGRAM INITIATED BY THE MANUFACTURER/DISTRIBUTOR NAMED ON THIS SHEET. IT IS NOT INTENDED TO CONSTITUTE PERFORMANCE INFORMATION CONCERNING THE PRODUCT. NO EXPRESS WARRANTY, OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE WITH RESPECT TO THE PRODUCT OR THE INFORMATION CONTAINED HEREIN.

Please note that several items were left out of section 9 because they do not affect the worker in the workplace. Partition coefficient: n-octanol/water; • Auto-ignition temperature; • Decomposition temperature and Odor threshold.