SECTION 1 - IDENTIFICATION

MANUF / DIST:

PREPARER / CONTACT: PREPARER PHONE: 24 HOUR EMERGENCY PHONE: MAJESTIC SOLUTIONS DISTRIBUTING CO 1001 CORPORATION PARKWAY SUITE 110 RALEIGH, N.C. 27610 PHIL TODD 919-212-1150 INFOTRAC 1-800-535-5053


RED MAX

TRADE NAME / SYNONYMS:

CHEMICAL NAME / SYNONYMS: CHEMICAL FAMILY: FORMULA: PRODUCT CODE: INTENDED USE: NOT APPLICABLE NOT APPLICABLE PROPRIETARY NOT APPLICABLE AUTOMOTIVE CLEANING CHEMICAL

SECTION 2 HAZARDOUS IDENTIFICATION

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM:





Signal Word: WARNING! - FOR HEALTH EFFECTS (Acute and Chronic): SEE SECTION 11

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

NAMES OF HAZARDOUS INGREDIENTS: See CFR29§1910.1200 (i)-(13) [exact % withheld as trade secret]					
CHEMICAL / COMMON NAME	CAS#	PERCENTAGE	PEL-OSHA	TLV-ACGIH	
Sodium Hydroxide	1310-73-2	<1	2mg/mg ³	2mg/m ³	
2 Butoxy Ethanol (Skin)	111-76-2	>1	50PPM	25PPM	
THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA):					

DHL rev 1/28/2021

MAJESTIC SOLUTIONS DISTRIBUTING CO

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID PROCEDURES:

- a) Skin Wash with running water.
- b) Eyes Flush with large amounts of water, lifting upper and lower lids occasionally.
- c) Inhalation If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet and get medical attention.
- d) Ingestion Immediately drink 2 glasses of water and induce vomiting by either giving IPECAC syrup or by placing fingers at the back of throat. Never give anything by mouth to an unconscious person. Get medical attention immediately.

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Not considered a fire hazard. SPECIAL FIRE FIGHTING PROCEDURES: None. UNUSUAL FIRE AND EXPLOSION HAZARDS: None HAZARDOUS DECOMPOSITION PRODUCTS: After water evaporates, burning may produce oxides of carbon, traces of sulfur and nitrogen oxides and various hydrocarbons.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Absorb the large spill on suitable absorbent. Wash the residue down the drain or pit with plenty of water. Small spills can be flushed down the drain with plenty of water. Eliminate the reason for spill.

INCOMPATIBILITY (Material To Avoid):

Avoid contact with acids and strong oxidizers such as chlorine, permanganate, etc.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

- a) Do not store under freezing conditions or above 120 degrees F.
- b) Protect from physical damage and keep tightly closed.
- c) Do not store near acids or acidic materials and oxidizers.
- d) Containers with concentrate should be marked slippery on floor surfaces

MAINTENANCE PRECAUTIONS:

When working with FLAMMABLE material electrically ground all equipment and use only non-sparking tools. OTHER PRECAUTIONS:

a) Containers, even those that have been emptied will retain product residue and vapors. Always obey hazard warnings.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: LOCAL EXHAUST: Below TLV(s)MECHANICAL (GENERAL): none SPECIAL: N/A OTHER: N/A RESPIRATORY PROTECTION: Not needed. PROTECTIVE GLOVES: Not mandatory but recommended OTHER PROTECTIVE EQUIPMENT: N/A OTHER ENGINEERING CONTROLS: Eye wash and quick drench facilities. WORK PRACTICES: Eye wash fountain and safety shower should be easily accessible. Discard properly such items as rags and trash soaked with the product. Provide

DHL rev 1/28/2021

MAJESTIC SOLUTIONS DISTRIBUTING CO

adequate ventilation.

HYGIENIC PRACTICES:

Avoid contact with eyes, skin and clothing. Avoid inhalation of product vapors. Wash thoroughly after handling and before eating, drinking or smoking. Remove contaminated clothing promptly and wash thoroughly before reused.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT (F):	>212	SPECIFIC GRAVITY (WATER=1):	1.040				
VAPOR PRESSURE (mmHg):	N/D	PERCENT VOLATILE BY VOLUME (%):	> 80				
VAPOR DENSITY (AIR=1):	N/D	EVAPORATION RATE (WATER=1):	1				
SOLUBILITY IN WATER	100%	FLASH POINT (Method Used):	None				
pH	10/11	FLAMMABLE LIMITS: LEL= N/A UEL=	N/A				

Melting pt-N/A /freezing pt 30+-°F/Relative density N/A

APPEARANCE, ODOR, VISCOSITY:: Red thin liquid, peculiar odor.

SECTION 10 STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION WILL NOT OCCUR THIS PRODUCT IS STABLE

SECTION 11. TOXICOLOGICAL INFORMATION

FOR NUMERICAL MEASURES OF TOXICITY SEE SECTION 3, COLUMNS (PEL-OSHA)AND(TLV-ACGIH)

HEALTH EFFECTS (Acute and Chronic): Alkaline Substance

Acute:

a) Eyes - Can cause severe irritation, redness, tearing, blurred vision.

- b) Skin Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.
- c) Inhalation mild irritation
- d) Ingestion Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic

a) Overexposure to glycol ethers (in its pure state) has been found to cause anemia, liver abnormalities, kidney damage, lung damage and blood abnormalities in laboratory animals.

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA)

PRIMARY ROUTES OF ENTRY: a) Skin b) Inhalation

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:

Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to product.

SECTION 12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: N/A 100% BIODEGRADABLE ECOTOXICOLOGICAL INFORMATION: N/A

SECTION 13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS:

Dispose of according to local, state and federal regulations for biodegradable soaps and detergents.

DHL rev 1/28/2021 MAJESTIC SOLUTIONS DISTRIBUTING CO

SECTION 14. TRANSPORT INFORMATION

THE FOLLOWING LINE MUST BE ON ALL LABELS AND SHIPPING PAPERS

COMPOUNDS, CLEANING LIQUID, 8, NA-1760, PK GP II, CORROSIVE, (sodium hydroxide)

SECTION 15. REGULATORY INFORMATION

THIS PRODUCT DOES NOT CONTAIN CARCINOGENS: (NTP, IARC, OSHA):

KEEP OUT OF THE REACH OF CHILDREN!

IN CLOSE COOPERATION OF THE US GOVERNMENT'S PAPER REDUCTION ACT, AND ALSO IN EFFORT TO PROVIDE FULL AND COMPLETE INFORMATION AS SUGGESTED BY THE OSHA GUIDELINES, AND KEEPING IN ALIGNMENT WITH THE SOCIETY for CHEMICAL HAZARD COMMUNICATION (SCHC) AND WE HAVE BEEN ABLE TO KEEP ALL IN 4 PAGES..

THESE SDS SHEETS ARE WRITTEN IN AN EFFORT TO PROVIDE INFORMATION TO THE WORKER IN THE WORKPLACE AND IN SUCH A WAY IT CAN BE UNDERSTOOD.

We have enjoyed many compliments as to the readability and understandable content, and take great pride in providing these Safety Data Sheets to the use of our customers.

The International Labour Organization has suggested 16 sections of the sheets, and we have re adjusted the 8 part, and rearranged the information, and renamed the sheets from MATERIAL Safety Data Sheets to SAFETY DATA SHEETS. THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE. IT IS PROVIDED FOR A CONTINUING SAFETY PROGRAM INITIATED BY THE MANUFACTURER/DISTRIBUTOR NAMED ON THIS SHEET. IT IS NOT INTENDED TO CONSTITUTE PERFORMANCE INFORMATION CONCERNING THE PRODUCT. NO EXPRESS WARRANTY, OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IS MADE WITH RESPECT TO THE PRODUCT OR THE INFORMATION CONTAINED HEREIN.

Please note that several items were left out of section 9 because they do not affect the worker in the workplace. Partition coefficient: n-octanol/water; • Auto-ignition temperature; • Decomposition temperature and Odor threshold.